

## Burner Type : AB - G 25

Fuel Type : Natural Gas

Combustion System : Double Stage

Operating Range : ( 802 ~ 3210 ) kW

( 690,000 ~ 2,760,000 ) kcal/h



Components	Supplied by	Technical data
Electromotor	Motogen	5.5 kW - ~ 380 V - 50 Hz - 3 Ph. - 2800 rpm
Air Damper Motor	Conectron	LKS 210
	Siemens	SQN 31
Control Box	Satronic	TMG 740
	Siemens	LFL 1.635
Gas Accessories	Solenoid Valve 1	Dungs - Krom - Honeywell Slow Opening , 1 Stage , 1"
	Solenoid Valve 2	Dungs - Krom - Honeywell Slow Opening , 1 Stage , 1 ½"
	Pilot Solenoid Valve	HoneyWell Fast Opening , 1 Stage , 1/2"
	Safety Solenoid Valve	HoneyWell Fast Opening , 1 Stage , 2"
Blower		355 * 120 - 38 mm
On Request	Control Panel	Completely Montaged
	Terminal Box	Terminals , On-off switch , Input phase indicator signals
Weight ( burner + gas line )		206 + 26 = 232 kg
Gas inlet pressure		( 50 - 150 ) m.bar
Gas inlet connection		DN 50 ( 2" )