

Burner Type : AB - G 30

Fuel Type : Natural Gas

Combustion System : Double Stage

Operating Range : (1021 ~ 4187) kW

(878,000 ~ 3,600,000) kcal/h



Components	Supplied by	Technical data
Electromotor	Motogen	7.5 kW - ~ 380 V - 50 Hz - 3 Ph. - 2800 rpm
Air Damper Motor	Connectron	LKS 210
	Siemens	SQN 31
Control Box	Satronic	TMG 740
	Siemens	LFL 1.635
Gas Accessories	Solenoid Valve 1	Dungs - Krom - Honeywell Slow Opening , 1 Stage , 1"
	Solenoid Valve 2	Dungs - Krom - Honeywell Slow Opening , 1 Stage , 1 ½"
	Pilot Solenoid Valve	HoneyWell Fast Opening , 1 Stage , 1/2"
	Safety Solenoid Valve	HoneyWell Fast Opening , 1 Stage , 2"
Blower		400 * 100 - 38 mm
On Request	Control Panel	Completely Montaged
	Terminal Box	Terminals , On-off switch , Input phase indicator signals
Weight (burner + gas line)		240 + 26 = 266 kg
Gas inlet pressure		(50 - 150) m.bar
Gas inlet connection		DN 50 (2")

- The Control Panel or Terminal Box are installed on customer request.